

## Strata Refuge Chamber Inspection

Exterior Inspection	Meets Requirements	Needs Attention	N/A	Comments
Site Conditions: Check roof control, ventilation, area free of obstruction.				
Physical Condition of Unit Note damage to the Chamber Skid that could impact performance.				
Tent Door Tamper Seal				
Maintenance Door Tamper Seal				
If Access Door is Unsealed	Meets Requirements	Needs Attention	N/A	Comments
Instructions Assure the laminated instructions are in place.				
Strobe Light				
Air Monitors				
System Inspection	Meets Requirements	Needs Attention	N/A	Comments
Temperature Read and record thermometer reading.				
Oxygen Gauge Determine required pressure based on temperature and actual.				
Scrubber Drive Gauge Determine required pressure based on temperature and actual.				
Purge Air Gauge Determine required pressure based on temperature and actual.				
Inflate Air Gauge Determine required pressure based on temperature and actual.				
Humidity Sensor Check color indicator.				



## Refuge Chamber Set-up Requirements

Exterior Inspection	Meets Requirements	Needs Attention	N/A	Comments
Distance Requirements: Within 1,000 feet of the working face-within 1-hour travel distance depending on height.				
Location Not in direct line sight of the face.				
Location Not placed 500 feet radially from belt drives, take-ups, transfer points, air compressors, explosive magazines.				
Location Seals, entrances to abandoned areas, fuel, oil, or other flammable or combustible material storage.				
Site Conditions Check roof control, ventilation, area free of obstruction – allow door to open fully.				
Lifelines Ensure branchline from primary and secondary escapeway is connected to chamber exterior.				
Branchline and Chamber Indicators Ensure that branchline indicators and chamber indicators are in place.				
Reflective Sign A conspicuously marked sign with "Refuge" marked on the sign.				
Communication A two-way communication system that is part of the mine community system - primary/secondary phone lines.				
Emergency Door Tamper Seal				
Maintenance Door Tamper Seal				



<b>If Access Door is Unsealed</b>	<b>Meets Requirements</b>	<b>Needs Attention</b>	<b>N/A</b>	<b>Comments</b>
Instructions Assure the laminated instructions are in place.				
Strobe Light				
Air Monitors				
<b>System Inspection</b>	<b>Meets Requirements</b>	<b>Needs Attention</b>	<b>N/A</b>	<b>Comments</b>
Temperature Read and record thermometer reading.				
Oxygen Gauge Determine required pressure based on temperature and actual.				
Scrubber Drive Gauge Determine required pressure based on temperature and actual.				
Purge Air Gauge Determine required pressure based on temperature and actual.				
Inflate Air Gauge Determine required pressure based on temperature and actual.				
Humidity Sensor Check color indicator.				

*KEMI does not assume liability for the content of information contained herein. Safety and health remain your responsibility. This information is to be used for informational purposes only and not intended to be exhaustive or a substitute for proper training, supervision or manufacturers' instructions/recommendations. KEMI, by publication of this information, does not assume liability for damage or injury arising from reliance upon it. Compliance with this information is not a guarantee or warranty that you will be in conformity with any laws or regulations nor does it ensure the absolute safety of any person, place or object, including, but not limited to, you, your occupation, employees, customers or place of business.*



Making workers' comp work